

52. IWK


Internationales Wissenschaftliches Kolloquium
International Scientific Colloquium



PROCEEDINGS

| 10 - 13 September 2007

FACULTY OF COMPUTER SCIENCE AND AUTOMATION



COMPUTER SCIENCE MEETS AUTOMATION

VOLUME I

Session 1 - Systems Engineering and Intelligent Systems

Session 2 - Advances in Control Theory and Control Engineering

**Session 3 - Optimisation and Management of Complex
Systems and Networked Systems**

Session 4 - Intelligent Vehicles and Mobile Systems

Session 5 - Robotics and Motion Systems



Bibliografische Information der Deutschen Bibliothek

Die Deutsche Bibliothek verzeichnet diese Publikation in der deutschen Nationalbibliografie; detaillierte bibliografische Daten sind im Internet über <http://dnb.ddb.de> abrufbar.

ISBN 978-3-939473-17-6

Impressum

- Herausgeber: Der Rektor der Technischen Universität Ilmenau
Univ.-Prof. Dr. rer. nat. habil. Peter Scharff
- Redaktion: Referat Marketing und Studentische Angelegenheiten
Kongressorganisation
Andrea Schneider
Tel.: +49 3677 69-2520
Fax: +49 3677 69-1743
e-mail: kongressorganisation@tu-ilmenau.de
- Redaktionsschluss: Juli 2007
- Verlag: 
Technische Universität Ilmenau/Universitätsbibliothek
Universitätsverlag Ilmenau
Postfach 10 05 65
98684 Ilmenau
www.tu-ilmenau.de/universitaetsverlag
- Herstellung und Auslieferung: Verlagshaus Monsenstein und Vannerdat OHG
Am Hawerkamp 31
48155 Münster
www.mv-verlag.de
- Layout Cover: www.cey-x.de
- Bezugsmöglichkeiten: Universitätsbibliothek der TU Ilmenau
Tel.: +49 3677 69-4615
Fax: +49 3677 69-4602

© Technische Universität Ilmenau (Thür.) 2007

Diese Publikationen und alle in ihr enthaltenen Beiträge und Abbildungen sind urheberrechtlich geschützt. Mit Ausnahme der gesetzlich zugelassenen Fälle ist eine Verwertung ohne Einwilligung der Redaktion strafbar.

Preface

Dear Participants,

Confronted with the ever-increasing complexity of technical processes and the growing demands on their efficiency, security and flexibility, the scientific world needs to establish new methods of engineering design and new methods of systems operation. The factors likely to affect the design of the smart systems of the future will doubtless include the following:

- As computational costs decrease, it will be possible to apply more complex algorithms, even in real time. These algorithms will take into account system nonlinearities or provide online optimisation of the system's performance.
- New fields of application will be addressed. Interest is now being expressed, beyond that in "classical" technical systems and processes, in environmental systems or medical and bioengineering applications.
- The boundaries between software and hardware design are being eroded. New design methods will include co-design of software and hardware and even of sensor and actuator components.
- Automation will not only replace human operators but will assist, support and supervise humans so that their work is safe and even more effective.
- Networked systems or swarms will be crucial, requiring improvement of the communication within them and study of how their behaviour can be made globally consistent.
- The issues of security and safety, not only during the operation of systems but also in the course of their design, will continue to increase in importance.

The title "Computer Science meets Automation", borne by the 52nd International Scientific Colloquium (IWK) at the Technische Universität Ilmenau, Germany, expresses the desire of scientists and engineers to rise to these challenges, cooperating closely on innovative methods in the two disciplines of computer science and automation.

The IWK has a long tradition going back as far as 1953. In the years before 1989, a major function of the colloquium was to bring together scientists from both sides of the Iron Curtain. Naturally, bonds were also deepened between the countries from the East. Today, the objective of the colloquium is still to bring researchers together. They come from the eastern and western member states of the European Union, and, indeed, from all over the world. All who wish to share their ideas on the points where "Computer Science meets Automation" are addressed by this colloquium at the Technische Universität Ilmenau.

All the University's Faculties have joined forces to ensure that nothing is left out. Control engineering, information science, cybernetics, communication technology and systems engineering – for all of these and their applications (ranging from biological systems to heavy engineering), the issues are being covered.

Together with all the organizers I should like to thank you for your contributions to the conference, ensuring, as they do, a most interesting colloquium programme of an interdisciplinary nature.

I am looking forward to an inspiring colloquium. It promises to be a fine platform for you to present your research, to address new concepts and to meet colleagues in Ilmenau.



Professor Peter Scharff
Rector, TU Ilmenau



Professor Christoph Ament
Head of Organisation

CONTENTS

	Page
1 Systems Engineering and Intelligent Systems	
A. Yu. Nedelina, W. Fengler DIPLAN: Distributed Planner for Decision Support Systems	3
O. Sokolov, M. Wagenknecht, U. Gocht Multiagent Intelligent Diagnostics of Arising Faults	9
V. Nissen Management Applications of Fuzzy Control	15
O. G. Rudenko, A. A. Bessonov, P. Otto A Method for Information Coding in CMAC Networks	21
Ye. Bodyanskiy, P. Otto, I. Pliss, N. Teslenko Nonlinear process identification and modeling using general regression neuro-fuzzy network	27
Ye. Bodyanskiy, Ye. Gorshkov, V. Kolodyazhniy, P. Otto Evolving Network Based on Double Neo-Fuzzy Neurons	35
Ch. Wachten, Ch. Ament, C. Müller, H. Reinecke Modeling of a Laser Tracker System with Galvanometer Scanner	41
K. Lüttkopf, M. Abel, B. Eylert Statistics of the truck activity on German Motorways	47
K. Meissner, H. Hensel A 3D process information display to visualize complex process conditions in the process industry	53
F.-F. Steege, C. Martin, H.-M. Groß Recent Advances in the Estimation of Pointing Poses on Monocular Images for Human-Robot Interaction	59
A. González, H. Fernlund, J. Ekblad After Action Review by Comparison – an Approach to Automatically Evaluating Trainee Performance in Training Exercise	65
R. Suzuki, N. Fujiki, Y. Taru, N. Kobayashi, E. P. Hofer Internal Model Control for Assistive Devices in Rehabilitation Technology	71
D. Sommer, M. Golz Feature Reduction for Microsleep Detection	77

F. Müller, A. Wenzel, J. Wernstedt A new strategy for on-line Monitoring and Competence Assignment to Driver and Vehicle	83
V. Borikov Linear Parameter-Oriented Model of Microplasma Process in Electrolyte Solutions	89
A. Avshalumov, G. Filaretov Detection and Analysis of Impulse Point Sequences on Correlated Disturbance Phone	95
H. Salzwedel Complex Systems Design Automation in the Presence of Bounded and Statistical Uncertainties	101
G. J. Nalepa, I. Wojnicki Filling the Semantic Gaps in Systems Engineering	107
R. Knauf Compiling Experience into Knowledge	113
R. Knauf, S. Tsuruta, Y. Sakurai Toward Knowledge Engineering with Didactic Knowledge	119
 2 Advances in Control Theory and Control Engineering	
U. Konigorski, A. López Output Coupling by Dynamic Output Feedback	129
H. Toossian Shandiz, A. Hajipoor Chaos in the Fractional Order Chua System and its Control	135
O. Katernoga, V. Popov, A. Potapovich, G. Davydau Methods for Stability Analysis of Nonlinear Control Systems with Time Delay for Application in Automatic Devices	141
J. Zimmermann, O. Sawodny Modelling and Control of a X-Y-Fine-Positioning Table	145
A. Winkler, J. Suchý Position Based Force Control of an Industrial Manipulator	151
E. Arnold, J. Neupert, O. Sawodny, K. Schneider Trajectory Tracking for Boom Cranes Based on Nonlinear Control and Optimal Trajectory Generation	157

K. Shaposhnikov, V. Astakhov The method of ortogonal projections in problems of the stationary magnetic field computation	165
J. Naumenko The computing of sinusoidal magnetic fields in presence of the surface with bounded conductivity	167
K. Bayramkulov, V. Astakhov The method of the boundary equations in problems of computing static and stationary fields on the topological graph	169
T. Kochubey, V. Astakhov The computation of magnetic field in the presence of ideal conductors using the Integral-differential equation of the first kind	171
M. Schneider, U. Lehmann, J. Krone, P. Langbein, Ch. Ament, P. Otto, U. Stark, J. Schrickel Artificial neural network for product-accompanied analysis and control	173
I. Jawish The Improvement of Traveling Responses of a Subway Train using Fuzzy Logic Techniques	179
Y. Gu, H. Su, J. Chu An Approach for Transforming Nonlinear System Modeled by the Feedforward Neural Networks to Discrete Uncertain Linear System	185
3 Optimisation and Management of Complex Systems and Networked Systems	
R. Franke, J. Doppelhammer Advanced model based control in the Industrial IT System 800xA	193
H. Gerbracht, P. Li, W. Hong An efficient optimization approach to optimal control of large-scale processes	199
T. N. Pham, B. Wutke Modifying the Bellman's dynamic programming to the solution of the discrete multi-criteria optimization problem under fuzziness in long-term planning	205
S. Ritter, P. Bretschneider Optimale Planung und Betriebsführung der Energieversorgung im liberalisierten Energiemarkt	211
P. Bretschneider, D. Westermann Intelligente Energiesysteme: Chancen und Potentiale von IuK-Technologien	217

Z. Lu, Y. Zhong, Yu. Wu, J. Wu WSReMS: A Novel WSDM-based System Resource Management Scheme	223
M. Heit, E. Jennenchen, V. Kruglyak, D. Westermann Simulation des Strommarktes unter Verwendung von Petrinetzen	229
O. Sauer, M. Ebel Engineering of production monitoring & control systems	237
C. Behn, K. Zimmermann Biologically inspired Locomotion Systems and Adaptive Control	245
J. W. Vervoorst, T. Kopfstedt Mission Planning for UAV Swarms	251
M. Kaufmann, G. Bretthauer Development and composition of control logic networks for distributed mechatronic systems in a heterogeneous architecture	257
T. Kopfstedt, J. W. Vervoorst Formation Control for Groups of Mobile Robots Using a Hierarchical Controller Structure	263
M. Abel, Th. Lohfelder Simulation of the Communication Behaviour of the German Toll System	269
P. Hilgers, Ch. Ament Control in Digital Sensor-Actuator-Networks	275
C. Saul, A. Mitschele-Thiel, A. Diab, M. Abd rabou Kalil A Survey of MAC Protocols in Wireless Sensor Networks	281
T. Rossbach, M. Götze, A. Schreiber, M. Eifart, W. Kattaneq Wireless Sensor Networks at their Limits – Design Considerations and Prototype Experiments	287
Y. Zhong, J. Ma Ring Domain-Based Key Management in Wireless Sensor Network	293
V. Nissen Automatic Forecast Model Selection in SAP Business Information Warehouse under Noise Conditions	299
M. Kühn, F. Richter, H. Salzwedel Process simulation for significant efficiency gains in clinical departments – practical example of a cancer clinic	305

D. Westermann, M. Kratz, St. Kümmerling, P. Meyer Architektur eines Simulators für Energie-, Informations- und Kommunikations- technologien	311
P. Moreno, D. Westermann, P. Müller, F. Büchner Einsatzoptimierung von dezentralen netzgekoppelten Stromerzeugungs- anlagen (DEA) in Verteilnetzen durch Erhöhung des Automatisierungsgrades	317
M. Heit, S. Rozhenko, M. Kryvenka, D. Westermann Mathematische Bewertung von Engpass-Situationen in Transportnetzen elektrischer Energie mittels lastflussbasierter Auktion	331
M. Lemmel, M. Schnatmeyer RFID-Technology in Warehouse Logistics	339
V. Krugljak, M. Heit, D. Westermann Approaches for modelling power market: A Comparison.	345
St. Kümmerling, N. Döring, A. Friedemann, M. Kratz, D. Westermann Demand-Side-Management in Privathaushalten – Der eBox-Ansatz	351
4 Intelligent Vehicles and Mobile Systems	
A. P. Aguiar, R. Ghabchelloo, A. Pascoal, C. Silvestre , F. Vanni Coordinated Path following of Multiple Marine Vehicles: Theoretical Issues and Practical Constraints	359
R. Engel, J. Kalwa Robust Relative Positioning of Multiple Underwater Vehicles	365
M. Jacobi, T. Pfützenreuter, T. Glotzbach, M. Schneider A 3D Simulation and Visualisation Environment for Unmanned Vehicles in Underwater Scenarios	371
M. Schneider, M. Eichhorn, T. Glotzbach, P. Otto A High-Level Simulator for heterogeneous marine vehicle teams under real constraints	377
A. Zangrilli, A. Picini Unmanned Marine Vehicles working in cooperation: market trends and technological requirements	383
T. Glotzbach, P. Otto, M. Schneider, M. Marinov A Concept for Team-Orientated Mission Planning and Formal Language Verification for Heterogeneous Unmanned Vehicles	389

M. A. Arredondo, A. Cormack SeeTrack: Situation Awareness Tool for Heterogeneous Vehicles	395
J. C. Ferreira, P. B. Maia, A. Lucia, A. I. Zapaniotis Virtual Prototyping of an Innovative Urban Vehicle	401
A. Wenzel, A. Gehr, T. Glotzbach, F. Müller Superfour-in: An all-terrain wheelchair with monitoring possibilities to enhance the life quality of people with walking disability	407
Th. Krause, P. Protzel Verteiltes, dynamisches Antriebssystem zur Steuerung eines Luftschiffes	413
T. Behrmann, M. Lemmel Vehicle with pure electric hybrid energy storage system	419
Ch. Schröter, M. Höchemer, H.-M. Groß A Particle Filter for the Dynamic Window Approach to Mobile Robot Control	425
M. Schenderlein, K. Debes, A. Koenig, H.-M. Groß Appearance-based Visual Localisation in Outdoor Environments with an Omnidirectional Camera	431
G. Al Zeer, A. Nabout, B. Tibken Hindernisvermeidung für Mobile Roboter mittels Ausweichecken	437
 5 Robotics and Motion Systems	
Ch. Schröter, H.-M. Groß Efficient Gridmaps for SLAM with Rao-Blackwellized Particle Filters	445
St. Müller, A. Scheidig, A. Ober, H.-M. Groß Making Mobile Robots Smarter by Probabilistic User Modeling and Tracking	451
A. Swerdlow, T. Machmer, K. Kroschel, A. Laubenheimer, S. Richter Opto-acoustical Scene Analysis for a Humanoid Robot	457
A. Ahranovich, S. Karpovich, K. Zimmermann Multicoordinate Positioning System Design and Simulation	463
A. Balkovoy, V. Cacenkin, G. Slivinskaia Statical and dynamical accuracy of direct drive servo systems	469
Y. Litvinov, S. Karpovich, A. Ahranovich The 6-DOF Spatial Parallel Mechanism Control System Computer Simulation	477

V. Lysenko, W. Mintchenya, K. Zimmermann 483
Minimization of the number of actuators in legged robots using
biological objects

J. Kroneis, T. Gastauer, S. Liu, B. Sauer 489
Flexible modeling and vibration analysis of a parallel robot with
numerical and analytical methods for the purpose of active vibration damping

A. Amthor, T. Hausotte, G. Jäger, P. Li 495
Friction Modeling on Nanometerscale and Experimental Verification

Paper submitted after copy deadline

2 Advances in Control Theory and Control Engineering

V. Piwek, B. Kuhfuss, S. Allers
Feed drivers – Synchronized Motion is leading to a process optimization 503

K. Meissner / H. Hensel

A 3D process information display to visualize complex process conditions in the process industry

Human-machine Interface

1. Introduction

In the last few years, a clear increase in system complexity of production sites as a result of the technical developments in the process industry, and thus a not insignificant increase in the requirements of the operators of such systems, has been recorded. On the one hand, for cost reasons the degree of automation and the productivity of the systems have further increased, and on the other hand the number of system operators per system and shift have continued to be reduced. The information capacity to be supervised by an individual operator has thus been constantly rising [6]. The resulting mental load and the possible overloading of the operator described by Grams [4] result in an increasing error potential in the operator actions, particularly in emergency and stress situations. The solution methods already discussed in the technical literature in order to tackle this problem stretch on the one side from improved visualization, like the mass data display [3] or the 3D-visualization [8], which should unburden the user. On the other side, complex expert systems [1] were developed, which are supposed to actively support the operator during the processing by means of artificial intelligence methods, mathematical prognosis models and stored process knowledge [5].

In this paper, previous attempts at an improvement in visualization, in particular icon-based visualization [2] [7], are taken up and a new procedure with simple 3D icons is described. For this, the realizations of the cognitive science are to be used, in order to consider the abilities and the weaknesses of the human perception. It uses a cognitive scenic approach, which is to facilitate a recognizing and a classifying of critical process conditions or process tendencies of the operator. The second section presents the new icon and the imbedding into the 3D world. Here the cognitive scenic aspect of this

visualization method comes into being. The next section describes the process of the user evaluation and the conclusion forms a summary of the results as well as a look at further works.

2. Implementation

Based on the problems described above, a new type of icon based mass data display was developed. It contains a 3D view of several process values as figure 2 shows. Each value is represented by an icon made-up of a cylindrical symbol with an inner area, an outer ring, a trend line, a forecasting pointer and a label as shown in figure 1.




Figure 1: Design of the 3D visualization icon

The inner area shows the urgency of the operator intervention and changes his transparency. A clear area means that no intervention is necessary (figure 2a) and a red area represents a very high need of intervention by the operator (figure 2b). The colored outer ring represents the process value and shows its name in the legend. The forecasting pointer shows the operator the direction the process is running before and after an intervention. The trend line points up the history of the process value and the label will only be shown if the mouse pointer touches an icon. If a process value (e.g. Temp. T2) runs out of the limits, the inner area will change to red and the icon will enlarge by moving to the front. This scenic visualization indicates the importance of attention by the operator. Values close to the setpoint are smaller, with a transparent inner area and they are localized in the middle of the display. Therefore the operator can recognize the system state with one view only. If there are small icons in the middle of the display and outside the inner red area, the process is running within the specification [9].

In the test environment, the visualization is connected to the technical process via OPC. A self developed set of engineering tools gives the engineer the opportunity to generate the code for the visualization icons and to create the connection between the icons and the process values.




Figure 2: Views of the 3D process information display (3D-PID)

3. User Evaluation of the 3D process information display

Due to the range of the investigations and evaluations – altogether 92 questions in ten subject areas – only the most important results can be presented here. The entire results are the subject of a further publication, which will appear in due course. With the accomplished questioning, the possibilities of different representational forms for process data were compared with one another. The newly-developed 3D process information display was contrasted with the traditional representational forms of graphic displays, group pictures and curve representation. In the context of the evaluation, the implementation of the attributes shown in Section 2 and the following questions should be examined:

- How is the usefulness of the characteristics of the icon and the 3D-worlds evaluated?
- Is the navigation in the 3D-world reasonable for the user?

- How obstructive do the errors of the process topology seem?
- How is the overall acceptance of the new visualization system?

Except for the representation of the case history, whose use by the test persons was only partially recognized, all new characteristics of the 3D process information displays were highly evaluated, from positive to above average. This applies in particular to the representation of the urgency display. Navigation in the 3D world was regarded by the testers as unproblematic – this in particular due to the pre-defined observation points. In the view of the test persons, the recognition of abnormalities and the necessity of an intervention was greatly simplified and accelerated through this representation. Due to the connection to traditional process diagrams, the absence of the process topology in the 3D display is not evaluated negatively. The positive evaluation of the questions regarding the acceptance and the general impression of the 3D visualization system rounds off the results of the questioning. The system was consistently rated good to above average in these respects as well.

Parallel to the evaluation of the 3D visualization systems with the help of the questionnaire described above and testing at real systems, the visualization system was presented at various trade fairs, conferences and congresses. In the resulting discussions, in particular the two issues of process topology and coupling with the traditional visualization procedures were discussed. The problem of the strong abstraction of the visualization procedure and the resulting loss of the representation of the process topology was considered to be difficult. The general opinion was however that the gaining of additional information – like the urgency of an intervention, the speed and direction of the deviation and the quick detectability of process conditions – compensates for the loss of the process topology. The increased value of this representation method in contrast to the traditional visualization procedures was confirmed in the talks with experts regarding the function as a summary visualization. Through the coupling integrated in prototypes with the traditional visualization procedures, the requirement for a summary visualization is likewise fulfilled. Only the implementation of the 3D-world through VRML in prototypes was marked as problematic for reasons relating to performance.

4. Application of the 3-D Process Information Display

Having described the evaluation of the visualization system in the previous section, the process of the lime production, by means of which the 3D process information display was tested in practice, should be briefly considered at this point. The raw material for the production of quicklime is extracted through blasting operations in open-cast mining and transported by heavy-duty lorry or conveyor belt for processing. The lumps of calcium carbonate (CaCO_3) limestone are mixed with finer coal and filled into the top of a kiln. This lime-coal mixture slowly slides through the firing zones, individually fuelled by gas, oil or animal fat, in which the limestone is deacidified at a temperature of 1,000 °C to 1,300 °C. The quicklime is removed from the bottom of the kiln and transported to bunkers.

The process of lime production was chosen as many different process variables must be monitored in the kiln in order to ensure the quality of the lime. The process variables display varying high time constants, which complicate the monitoring and evaluation of the process state. In addition, the concentration of sensors for the monitoring of the process parameters within the processor is very high. This effect has up to now also been negative for the use of conventional display processes, as the process graphics were very overlaid and confusing. For this reason, it was suggested that the 3D process information display was deployed as a layered representation, and thus make the quality-relevant process data and information more quickly and simply available to the operator. Both the downtime of the entire plant as well as the reaction times during disruptions could be reduced through the use of the 3D process information display.

5. Summary and Perspective

Through the investigations described in Section 2 and the procedure presented in Section 3, it could be shown that an icon-based cognitive scenic visualization can provide the user, in a simple manner, with a summary representation of the information required to assess the process state. The evaluation in Section 3 shows a high acceptance of the abilities of the 3D-PID by operators and students. The operator is relieved from the influence of stress, allowing potential sources of errors to be minimized. Cognitive scenic visualization should not replace existing visualization forms

but rather supplement them, and be understood as abstract and superior visualization components. The number of markers recognizable by the operator as problem-free, the influence of three-dimensional visualization on the mental load of the operator and the possibilities of navigation in the three-dimensional information area are the subject of further investigations.

References:

- [1] Berheide, W.; Dörfel, G.; Döring, B.: Wissensbasierte Benutzerunterstützung in komplexen Mensch-Maschine-Systemen. In: *Verlässlichkeit von Mensch-Maschine-Systemen*; Hrsg. Willumeit, H.-P.; Kolrep, H.; Berlin: Technische Universität Berlin, 1995, pp. 61 – 72
- [2] Chernoff, H.: The Use of Faces to Represent Points in k-Dimensional Space Graphically. *Journal of American Statistical Association*, Vol. 68, (1973), pp. 361 – 368
- [3] Elzer, P. F.: Neuere Entwicklungen auf dem Gebiet der Mensch-Maschine-Schnittstellen: *at - Automatisierungstechnik*, 49 (2001), No. 4; München: Oldenbourg, pp. 178 – 186
- [4] Grams, T.: Bedienfehler und ihre Ursachen (Teil 1). In: *atp – Automatisierungstechnische Praxis*, Vol. 40 (1998), No. 3; München: Oldenbourg, pp. 53 – 56
- [5] Johannsen, G.: Architecture of Man-Machine Decision Making Systems. In: *Intelligent Decision Support in Process Environments*, Hrsg. Hollnagel, E.; Mancini, G.; Woods, D.D.: Berlin, New York: Springer, 1986, pp. 328 – 339
- [6] Komischke, T.: Informationsüberflutung in der Prozessführung. In: *atp – Automatisierungstechnische Praxis*, Vol. 45 (2003), No. 9; München: Oldenbourg, pp. 74 – 79
- [7] Pickett, R. M.; Grinstein, G.: Iconographics Displays for Visualization Multidimensional Data. *Proceedings IEEE Conference on Systems, Man and Cybernetics*, Peking, 1988, pp.514 – 519
- [8] Wittenberg, C.: Das Konzept der virtuellen Prozessvisualisierung für die industrielle Prozessführung. In: *at – Automatisierungstechnik*, Vol. 50 (2002), No. 4; München: Oldenbourg, pp. 178 – 186.
- [9] Meißner, K.; Hensel, H.: Visualisierung komplexer Prozesszustände durch den Einsatz von 3-D-Methoden. Hrsg. VDI, VDI-Berichte 1883 (2005), Düsseldorf, VDI-Verlag, pp. 91 – 98,

Authors:

Dipl.-Ing. (FH) Knut Meissner
Institute for Computer Science and Automation Systems
Dornbergsweg 2
38855 Wernigerode
Phone: ++49 3943 6259-745
Fax: ++49 3943 6259-747
Email: kmeissner@hs-harz.de

Prof. Dr.-Ing. Hartmut Hensel
University of Applied Studies and Research
Friedrichstraße 57 – 59
38855 Wernigerode
Phone: ++49 3943 659 313
Fax: ++49 3943 659 399
Email: hhensel@hs-harz.de